

PUMP, VARIABLE DELIVERY

PVV-200 or 250

"P-3--" or "P-E--" CONTORLS

ENGINEERING




1

Installation Drawing

Triple Pressure Compensator Controls


PVV-200/250-BIU PUMP (SHOWN) PVV-200/250-B1S PUMP WITH P-3__ CONTROL (SHOWN) AND P-E_ CONTROL





OP-1 & OP-2 = PORT OR1
OP-3 & OP-4 = IN 4-WAY VALVE
OP-5 = PORT BO
OP-6 = PORT OR2
OP-14 = PORT TO

- NOTES:

 1. PUMPS DESIGNED FOR ONE-WAY SERVICE ARE DIMENSIONED AS SHOWN.
 - 2. THESE UNITS ARE DESIGNED TO RUN CASE FULL OF FLUID AT ALL TIMES. FILL CASE BEFORE STARTING AND CONNECT DRAIN LINES ACCORDINGLY.
 - NUMERICAL DIMENSIONS ARE GIVEN IN INCHES/[MM].
 - 4. NET WEIGHT: P-3... CONTROL
 415 LBS (188 KG) SIDE PORTED (SHOWN)
 390 LBS (177 KG) REAR PORTED
 P-E... CONTROL
 425 LBS (193 KG) SIDE PORTED
 400 LBS (181 KG) REAR PORTED
 - W/ HP LIMITER ADD 20 LBS (9 KG) W/ LOAD SENSE ADD 10 LBS (4.5 KG)
 - 5. FOR BASIC PUMP DIMENSIONS SEE: DS-47939
 - 6. LEFTHAND (CCW) VERSION IS SHOWN.
 FOR RIGHTHAND (CW) VERSION, THE CONTROL
 CAPS AND VOLUME STOPS WILL BE ON
 THE OPPOSITE SIDES. ASSUMING THAT
 THE OUTLET IS ON THE TOP.







Telephone: Fax:

(414) 327-1700 (414) 327-0532

OILGEAR 2300 So. 51st. Street Milwaukee, WI USA 53219

Reissued: June, 2004 DS-M47566-B



PUMP, VARIABLE DELIVERY PVV-200 or 250

"P-3--" or "P-E--" CONTROLS

ENGINEERING



2

Circuits

Triple Pressure Compensator Controls

